



	<b></b>		$\mathbf{i}$	jijk.			
	backing thickness μm	total thickness µm	adhesion N/cm	breaking load N/cm	elongation at break %	heavy weight packaging	available colours
NARFIL 500	28	120	> 8	> 220		•	$\oslash$
NARGLASS 532	28	120	> 8	> 170		•	$\oslash$
NARGLASS 539	28	130	> 8	> 220		•	$\oslash$
NARSTRAP 520 AR / BI	50	72	> 2,4	> 160	> 27	•	• 0
NARSTRAP 540 NE	75	98	> 2,4	> 240	> 27	•	•

⊘ transparent ● orange

black



NAR S.P.A. Legnaro (PADOVA) ITALY www.nar-spa.com It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it. The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nar shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product vitability to the specific condition of use. Additional indications are available in the last edition of the booklet "Recommendation regarding choice, storing and use of pressure sensitive tapes" published by Federazione Gomma Plastica.



www.nar-spa.com/ technical-notes.html

# NARFIL 500

INFORMATIVE DATA SHEET



## COMPOSITION

BACKING: biaxially oriented polypropylene film reinforced with longitudinal glass fibres ADHESIVE: synthetic rubber / hydrocarbonic resins CORE: recycled paper and paperboard

### SUITABLE FOR

Heavy packaging; binding things; palletizing

## AVAILABLE COLOURS

Transparent

The high performance hot melt adhesive and the glass fiber reinforced backing make this product the ideal choice for all packaging needs, also the heaviest.



ADHESION > 8 N/cm



BREAKING LOAD > 220 N/cm

HEAVY WEIGHT PACKAGING

ORGANIC SOLVENTS FREE











## NARGLASS 532

INFORMATIVE DATA SHEET

## HEAVY DUTY

## COMPOSITION

BACKING: biaxially oriented polypropylene film reinforced with cross weaved glass fibres ADHESIVE: synthetic rubber / hydrocarbonic resins CORE: recycled paper and paperboard

## SUITABLE FOR

Heavy packaging; binding things; palletizing

## AVAILABLE COLOURS

Transparent

The high performance hot melt adhesive and the glass fiber reinforced backing makes this product the ideal choice for all packaging needs, also the heaviest.



TOTAL THICKNESS 120 μm



BREAKING LOAD > 170 N/cm

HEAVY WEIGHT PACKAGING

ORGANIC SOLVENTS FREE











# NARGLASS 539

INFORMATIVE DATA SHEET

## HEAVY DUTY

## COMPOSITION

BACKING: biaxially oriented polypropylene film reinforced with cross weaved glass fibres ADHESIVE: synthetic rubber / hydrocarbonic resins CORE: recycled paper and paperboard

## SUITABLE FOR

Heavy packaging; binding things; palletizing

## AVAILABLE COLOURS

Transparent

The high performance hot melt adhesive and the glass fiber reinforced backing make this product the ideal choice for all packaging needs, also the heaviest.



TOTAL THICKNESS 130 μm



BREAKING LOAD > 220 N/cm

HEAVY WEIGHT PACKAGING

ORGANIC SOLVENTS FREE











## NAR STRAP 520 AR

INFORMATIVE DATA SHEET

## HEAVY DUTY

### COMPOSITION

BACKING: monoaxially oriented polypropylene ADHESIVE: natural rubber / hydrocarbonic resins / solvent CORE: recycled paper and paperboard

### SUITABLE FOR

Heavy packaging; binding things; palletizing

## AVAILABLE COLOURS

Orange

The natural rubber adhesive, together with the high performances of the monoaxially oriented support, make this product particularly suitable for palletizing and stocking heavy and bulky packages.



TOTAL THICKNESS 72 μm



BACKING THICKNESS 50 μm

>	BREAKING LOAD
	> 160 N/cm

HEAVY WEIGHT PACKAGING











# NAR STRAP 520 Bl

INFORMATIVE DATA SHEET



## COMPOSITION

BACKING: monoaxially oriented polypropylene ADHESIVE: natural rubber / hydrocarbonic resins / solvent CORE: recycled paper and paperboard

### SUITABLE FOR

Heavy packaging; binding things; palletizing

## AVAILABLE COLOURS

White

The natural rubber adhesive, together with the high performances of the monoaxially oriented support, make this product particularly suitable for palletizing and stocking heavy and bulky packages.



TOTAL THICKNESS 72 μm



BACKING THICKNESS 50 μm

>	BREAKING LOAD
	> 160 N/cm

HEAVY WEIGHT PACKAGING



NAR S.P.A. Legnaro (PADOVA) ITALY www.nar-spa.com







## NAR STRAP 540 NE

INFORMATIVE DATA SHEET

## HEAVY DUTY

## COMPOSITION

BACKING: monoaxially oriented polypropylene ADHESIVE: natural rubber / hydrocarbonic resins / solvent CORE: recycled paper and paperboard

### SUITABLE FOR

Heavy packaging; binding things; palletizing



## AVAILABLE COLOURS

Black

The natural rubber adhesive, together with the high performances of the monoaxially oriented support, make this product particularly suitable for palletizing and stocking heavy and bulky packages.



TOTAL THICKNESS 98 μm



BACKING THICKNESS 75  $\mu m$ 

## HEAVY WEIGHT PACKAGING



NAR S.P.A. Legnaro (PADOVA) ITALY www.nar-spa.com





