



NARPRINT 165

INFORMATIVE
DATA SHEET



MADE IN ITALY

PRINTED TAPES

COMPOSITION

BACKING: printed polyvinylchloride (PVC) film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers; sealing of recycled; cardboard boxes.

AVAILABLE COLOURS

Red - orange - black - white - yellow - green - light blue -
dark blue - fluo orange

The excellent mechanical characteristics of resistance, plasticity and adhesion, combined with silent unwinding, make this tape suitable for all packaging applications and traditional uses.




MEDIUM WEIGHT PACKAGING



HAND DISPENSER



WATER RESISTANT



BACKING THICKNESS
37 μ m



PRINTED TAPE



SILENT
UNWINDING



NAR S.P.A.
Legnaro (PADOVA)
ITALY
www.nar-spa.com

Membro di:















PRINTED TAPES

INFORMATIVE
DATA SHEET



| |  backing thickness µm |  total thickness µm |  adhesion N/cm |  breaking load N/cm |  elongation at break % |  available colours |  medium weight packaging |  light weight packaging |  automatic sealing machine |  suitable for low temperatures packaging |
|------------------|---|---|--|---|--|---|---|--|---|---|
| POLIPRINT 240 | 28 | 47 | > 2,0 | > 39 | > 116 | ● ○ ⊗ | | • | • | • |
| POLINARPRINT 260 | 32 | 51 | > 2,0 | > 45 | > 116 | ● ○ ⊗ | • | | • | • |
| POLINARPRINT 265 | 32 | 51 | > 2,0 | > 45 | > 116 | ● ● ● ● ● ● ● ● | • | | • | • |
| NARPRINT 140 | 32 | 51 | > 1,5 (BI) | > 45 | > 48 | ● ○ ⊗ | • | | | |
| | | | > 1,8 (AV TR) | | | | | | | |
| NARPRINT 165 | 37 | 56 | > 1,8 | > 50 | > 48 | ● ● ● ● ● ● ● ● | • | | | |
| NARPOUCH 240 | 28 | 47 | n.r. | > 39 | > 116 | ⊗ | | | | |
| NARPOUCH 260 | 32 | 51 | n.r. | > 45 | > 116 | ⊗ | | | | |
| RENEWA® TAPE 465 | 58 | 135 | > 2,2 | > 31 | > 7 | ● ○ | | • | • | |

● brown ○ white ⊗ transparent ● red ● orange ● black ● yellow ● green ● light blue ● blue ● fluo orange



NAR S.P.A.
Legnaro (PADOVA) ITALY
www.nar-spa.com

It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it. The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nar shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product suitability to the specific condition of use. Additional indications are available in the last edition of the booklet "Recommendation regarding choice, storing and use of pressure sensitive tapes" published by Federazione Gomma Plastica.



[www.nar-spa.com/
technical-notes.html](http://www.nar-spa.com/technical-notes.html)